

BARRETT FIREARMS

RIFLES

OPTICS

BARRETT STORE

TRAINING

AMMUNITION

FORUMS

OUR COMPANY

SERVICE & SUPPORT

**BORS**

BORS

EXPANDED BORS VIEW

Forum	Topic
FORUM	
General	
General discussion (5 Viewing)	352
Shim and Tell post your pic and vid	76
Legislation and 2nd Amendment	147
Barrett Rifles	
Model 90A/M102 (4 Viewing)	186

SCOPE RINGS
30mm

4 HEIGHTS

SCOPE RINGS

BORS™**MSRP OF BORS ONLY: \$1599.00 *****MSRP OF BORS WITH LEUPOLD® MARK 4: \$2769.00 ***

BORS is an integrated electronic ballistic computer that mounts directly on your riflescope and couples to the elevation knob. Just turn the elevation knob until the LCD displays the target's range. The BORS' three internal sensors will have automatically calculated your ballistic solution. It compensates for aiming up or down, temperature, and barometric pressure changes. It even tells you if the rifle is canted. Place the crosshair on the target and fire with first-round confidence.

The BORS kit includes the Barrett Ballistic PC Software and the BORS data cable that allows the user to program custom loads on their PC or laptop and transfer them directly to their BORS ballistic table calculations

BORS. It adds science to the rifleman's skill.

*** MSRP for U.S. civilian sales.**

- * IMPROVED BALLISTIC TABLE CALCULATIONS
- * MULTI LANGUAGE SUPPORT

**(CLICK TO DOWNLOAD)****COMPATIBLE SCOPES**

- Leupold® Mark IV 3.5-10x40mm LR/T M1
- Leupold® Mark IV 3.5-10x40mm LR/T M1
- Leupold® Mark IV 4.5-14x50mm LR/T M1
- Leupold® Mark IV 6.5-20x50mm LR/T M1
- Leupold® Mark IV 8.5-25x50mm LR/T M1
- Leupold® Mark IV 8.5-25x50mm ER/T M1
- Nightforce™ 8-32x56mm NXS 50 and 56mm objectives without "Zero-Stop"

Buy Now



PDF DOCUMENTS

[View PDF Manual](#)

[View PDF BORS Cartridge Tables](#)

[View PDF Barrett Ballistic Software Quick Start Guide](#)

[View PDF Shooting Times](#)

[View PDF Precision Shooting](#)

- Nightforce™ 3.5-15x NXS 50 and 56mm objectives without “Zero-Stop”
- Nightforce™ 5.5-22x NXS 50 and 56mm objectives without “Zero-Stop”
- Schmidt Bender 5-25x56mm PM II III with .1MRAD adjustments

SPECIFICATIONS

Operating Temperature Range- -4 thru 158 F (-20 C thru 70C)
 Weight- 13oz (370 grams)
 Display- 2 lines, 12 characters liquid crystal
 Buttons- 4 button keypad
 Operating Altitude- -1,000 thru 20,000 feet (-300 thru 6,100m)
 Tilt Range- -90 thru +90 degrees (2 degrees resolution)
 Battery- CR-123 Lithium
 Battery Life- 30 hours

FEATURES & ACCESSORIES

Barrett Ballistic Software
 USB to BORS data connection cable
 30 mm Zero-Gap™ Scope Rings (when purchased with or with out scope)
 100+ preloaded cartridge tables
 Tool Kit
 CR-123 Lithium Battery



[Printer Friendly page](#)



